



Indoor RF passives

Galvanic Isolators

GIS-103B

GIS isolators are used to galvanically isolate the coaxial access network from subscribers premises. They prevent problems caused by potential differences from occurring on sensitive devices like LCD and Plasma screens, VoIP and cable modems, when connected directly to system outlet. All the isolators withstand 2120VDC, 230VAC.

Features

- Frequency range up to 1000 MHz
- Outstanding RF performance
- 100% HI-POT test in production
- Press-in sealing technology with Aluminum lid for corrosion protection
- Blocking capacitors on all output ports for DC/HUM protection

One of Teleste's unique and award winning superior performance passives designed for easy installation and reliability.

TELESTE

INDOOR RF PASSIVES / GIS-103B

ELECTRICAL SPECIFICATIONS				
INSERTION LOSS (dB, Max.) - IN to OUT				
Frequency (MHz)				
5 - 10		0.8		
10 - 40		0.8		
40 - 470		0.8		
470 - 862		0.9		
862 - 1000		0.9		
RETURN LOSS (dB, Min.) - IN				
5 - 50		19.0		
50 - 1000		18.0		
RETURN LOSS (dB, Min.) - OUT				
5 - 50		19.0		
50 - 1000		18.0		
GENERAL SPECIFICATIONS				
Frequency range (MHz)	5 - 1000 MHz		Nominal Impedance	75 Ohm
Operating temperature	-20 ° to +60 °C		Dimensions (L x W x D)	47.8 x 59 x 20 mm
Safety Isolation	2120 VDC	Inner conductor Input to Inner conductor Output Leakage current ≤ 0.7 mA, ≥ 1 minute Outer conductor Input to Outer conduct Output Leakage current ≤ 0.7 mA, ≥ 1 minute		
	230 VAC RMS, 50/60 Hz	Inner conductor Input to Inner conductor Output Leakage current ≤ 2.0 mA RMS Outer conductor Input to Outer conduct Output Leakage current ≤ 2.0 mA RMS		
Electromagnetic Compatibility ⁽¹⁾ (dB, Min.)		5 - 8 8 - 10 10 - 300 300 - 470 470 - 1000		100.0 80.0 85.0 80.0 75.0
NOTES				
(1) EMC, exceeding Class A acc. to IEC 60728-2				
BLOCK DIAGRAM				
ORDERING INFORMATION				
GIS-103B		1-way Galvanic isolator 0.5dB, 5-1000 MHz		

TELESTE**TELESTE CORPORATION**
www.teleste.com

GIS-103B_20220118

Copyright © 2022 Teleste Corporation. All rights reserved. Teleste and the Teleste logo are registered trademarks of Teleste Corporation.
Other product and service marks are property of their respective owners.

Teleste reserves the right to make changes to any features and specifications of the products without prior notice. Although the information in this document has been reproduced in good faith, the contents of this document are provided "as is". Teleste makes no warranties of any kind in relation to the accuracy, reliability or contents of this document, except as required by applicable law.