



CUSTOMER DROP SOLUTIONS

Customer Drop Series - FMD Range

enlighten **TEN-FMD1**

Underground Customer Drop Enclosure

The TEN-FMD1 is a 8/16 customer connection IP68 enclosures, part of the highly versatile FMD range. Its modular design allows flexibility for splicing, splitting and customer connections with multiple flexible cable entry ports. The FMD1 is suitable for underground, aerial, pole and wall mounting applications.

Features

- Unique IP68 design
- Up to 16 customer connection adapters (LC)
- Up to 144 splices; 36 splices per 4 cassettes
- Support for splitter on adapter cassette
- 24 cable entry ports supporting 2-12mm cables
- Suitable for underground, aerial, pole and wall mounting applications



TELESTE

enlighten FTTx PASSIVES / CUSTOMER DROP SERIES

ENCLOSURE SPECIFICATION			
Dimension	248 x 175 x 75mm (L x W x H)	Material	PP+GF (Housing, Lid & Latches) ABS Plastic (Internals)
Capacity	144 fibres	Splice trays	4pcs x 36 fibres
Cable ports	Up to a total of 24 ports in multiple configurations available	Cable diameters	2 - 12mm
Operating temperature	-20 ° to + 70 °C	Rating	IP68
Net weight	650 grams (Excluding Grommets)		
IMAGE GALLERY			
			
ORDERING INFORMATION			
P/N	DESCRIPTION		
TEN-FMD1	16 customer drop connection point, IP68		



TELESTE CORPORATION
www.teleste.com

Underground Customer Drop Enclosure TEN-FMD1_240903
Copyright © 2024 Teleste Corporation. All rights reserved. Teleste and the Teleste logo are registered trademarks of Teleste Corporation. Other product and service marks are property of their respective owners. Teleste reserves the right to make changes to any features and specifications of the products without prior notice. Although the information in this document has been reproduced in good faith, the contents of this document are provided "as is". Teleste makes no warranties of any kind in relation to the accuracy, reliability or contents of this document, except as required by applicable law.